



# Flange Units – Pressed Steel 3 Bolt & 4 Bolt


## FHSPFZ200 / FHSPFFZ200 Series Set Screw Locking




- Two light duty, self-aligning pressed steel housings
- Narrow inner ring bearing
- Zinc plated stamped steel (shown)
- Non-plated, raw stamped steel available (FHSPFR/FHSPFFR Series)
- Non-lubricatable unit (shown)
- Lubricatable unit available (Add "G" suffix to end of part number)
- Standard seal: RST tight riding, full cover, metal shroud seals



FHSPFZ200



FHSPFFZ200



Optional seals: See page 85

### FHSPFZ200 3-Bolt

Unit No.	Shaft Diam.	Dimensions <small>in mm</small>								Bolt Size In.	Bearing No.	Housing No.
		a	e	g	c	s	f	Bi	n			
FHSPFZ201 -8 FHSPFZ201 -12mm FHSPFZ202 -9 FHSPFZ202 -10 FHSPFZ202 -15mm FHSPFZ203 -11 FHSPFZ203 -17mm	1/2 12mm 9/16 5/8 15mm 11/16 17mm	3 3/16 81	2 1/2 64	.074 1.9	9/16 14	9/32 7	1 15/16 49	0.8858 22.500	0.256 6.50	1/4	FHS201 -8 FHS201 -12mm FHS202 -9 FHS202 -10 FHS202 -15mm FHS203 -11 FHS203 -17mm	PF-3Z
FHSPFZ204 -12 FHSPFZ204 -13 FHSPFZ204 -20mm	3/4 13/16 20mm	3 9/16 90	2 13/16 71	.083 2.1	5/8 16	11/32 9	2 3/16 56	0.9843 25.000	0.295 7.50	5/16	FHS204 -12 FHS204 -13 FHS204 -20mm	PF-4Z
FHSPFZ205 -12 FHSPFZ205 -13 FHSPFZ205 -14 FHSPFZ205 -15 FHSPFZ205 -16 FHSPFZ205 -25mm	3/4 13/16 7/8 15/16 1 25mm	3 3/4 95	3 76	.083 2.1	11/16 17	11/32 9	2 3/8 66	1.0630 27.000	0.295 7.50	5/16	FHS205 -12 FHS205 -13 FHS205 -14 FHS205 -15 FHS205 -16 FHS205 -25mm	PF-5Z
FHSPFZ206 -17 FHSPFZ206 -18 FHSPFZ206 -19 FHSPFZ206 -20 FHSPFZ206 -30mm	1 1/16 1 1/8 1 3/16 1 1/4(s) 30mm	4 7/16 113	3 9/16 90	.104 2.6	11/16 17	13/32 10	2 13/16 71	1.1811 30.000	0.354 9.00	3/8	FHS206 -17 FHS206 -18 FHS206 -19 FHS206 -20 FHS206 -30mm	PF-6Z
FHSPFZ207 -20 FHSPFZ207 -21 FHSPFZ207 -22 FHSPFZ207 -23 FHSPFZ207 -35mm	1 1/4 1 5/16 1 3/8 1 7/16 35mm	4 13/16 122	3 15/16 100	.104 2.6	3/4 19	13/32 10	3 3/16 81	1.2598 32.000	0.374 9.50	3/8	FHS207 -20 FHS207 -21 FHS207 -22 FHS207 -23 FHS207 -35mm	PF-7Z

### FHSPFFZ200 4-Bolt

FHSPFFZ207 -20 FHSPFFZ207 -21 FHSPFFZ207 -22 FHSPFFZ207 -23 FHSPFFZ207 -35mm	1 1/4 1 5/16 1 3/8 1 7/16 35mm	4 13/16 122.3	3 15/16 100	.104 2.6	3/4 20.2	13/32 10.4	3 3/16 81	1.2598 32.000	0.37 9.50	3/8	FHS207 -20 FHS207 -21 FHS207 -22 FHS207 -23 FHS207 -35mm	PFF-7Z
FHSPFFZ208 -24 FHSPFFZ208 -25 FHSPFFZ208 -40mm	1 1/2 1 9/16 40mm	5 13/16 148	4 11/16 119	.134 3.3	13/16 20.2	17/32 13.5	3 9/16 90	1.4961 38.000	0.43 11.00	1/2	FHS208 -24 FHS208 -25 FHS208 -40mm	PFF-8Z
FHSPFFZ209 -26 FHSPFFZ209 -27 FHSPFFZ209 -28 FHSPFFZ209 -45mm	1 5/8 1 11/16 1 3/4 45mm	5 7/8 149	4 3/4 121	.134 3.4	7/8 22	17/32 13	3 13/16 90	1.5551 39.500	0.43 11.00	1/2	FHS209 -26 FHS209 -27 FHS209 -28 FHS209 -45mm	PFF-9Z
FHSPFFZ210 -29 FHSPFFZ210 -30 FHSPFFZ210 -31 FHSPFFZ210 -32 FHSPFFZ210 -50mm	1 13/16 1 7/8 1 15/16 2 50mm	6 1/8 156	5 127	.149 3.8	7/8 22	17/32 13	4 102	1.7165 43.600	0.43 11.00	1/2	FHS210 -29 FHS210 -30 FHS210 -31 FHS210 -32 FHS210 -50mm	PFF-10Z
FHSPFFZ211 -32 FHSPFFZ211 -33 FHSPFFZ211 -34 FHSPFFZ211 -35 FHSPFFZ211 -55mm	2 2 1/16 2 1/8 2 3/16 55mm	6 9/16 167	5 7/16 138	.149 3.8	15/16 24	17/32 13	4 7/16 113	1.81 45.90	0.49 12.50	1/2	FHS211 -32 FHS211 -33 FHS211 -34 FHS211 -35 FHS211 -55mm	PFF-11Z

Stamped housings can be made in AISI 304 stainless steel. Combine with stainless steel bearing for maximum corrosion resistance:  
Example: SSFHSPF205-16

Standard Mounted Units