





- Duty:** Standard
- Rolling Elements:** Ball
- Housing:** Cast Iron Piloted Flange Cartridge
- Self Alignment:** +/- 2 Degrees
- Lock:** SKWEZLOC® Locking Collar
- Seal:** Felt
- Optional Seal:** Contact
- Temperature:** -20° to 220° F



## SFC-T Series Standard Duty Piloted Flange Cartridge- SKWEZLOC Locking Collar - Inch

| BORE DIAMETER<br>inch | PART No. | BEARING INSERT No. | BASIC DYNAMIC RATING<br>lb/N | DIMENSIONS inch / mm |       |         |      |        |        |         |       |       |         | BOLT SIZE | UNIT Wt.<br>lb/kg |
|-----------------------|----------|--------------------|------------------------------|----------------------|-------|---------|------|--------|--------|---------|-------|-------|---------|-----------|-------------------|
|                       |          |                    |                              | A                    | BC    | D       | G    | H      | J      | L       | N     | O     | P       |           |                   |
| 1 1/8                 | SFC-18T  | 2-12T              | 4381                         | 4 3/8                | 3 5/8 | 1 11/64 | 3/8  | 1 3/8  | 1 5/8  | 2 3/16  | 5/8   | 1/4   | 3.000   | 5/16      | 3.2               |
| 1 3/16                | SFC-19T  | 2-13T              | 19487                        | 111.1                | 92.1  | 29.8    | 9.5  | 34.9   | 41.3   | 55.6    | 15.9  | 6.4   | 76.200  |           | 1.45              |
| 1 1/4                 | SFC-20RT | 1-14T              |                              |                      |       |         |      |        |        |         |       |       |         |           |                   |
| 1 1/4                 | SFC-20T  | 2-14T              | 5782                         | 5                    | 4 1/8 | 1 9/32  | 3/8  | 1 3/8  | 1 3/4  | 2 7/16  | 11/16 | 3/8   | 3.375   | 3/8       | 4.2               |
|                       |          |                    | 25718                        | 127.0                | 104.8 | 32.5    | 9.5  | 34.9   | 44.5   | 61.9    | 17.5  | 9.5   | 85.725  |           | 1.91              |
| 1 3/8                 | SFC-22T  | 2-16T              | 5782                         | 5                    | 4 1/8 | 1 9/32  | 3/8  | 1 3/8  | 1 3/4  | 2 9/16  | 11/16 | 3/8   | 3.375   | 3/8       | 4.2               |
| 1 7/16                | SFC-23T  | 2-17T              | 25718                        | 127.0                | 104.8 | 32.5    | 9.5  | 34.9   | 44.5   | 65.1    | 17.5  | 9.5   | 85.725  |           | 1.91              |
| 1 1/2                 | SFC-24T  | 2-18T              | 7340                         | 5 1/4                | 4 3/8 | 1 25/64 | 7/16 | 1 9/16 | 2      | 2 11/16 | 3/4   | 7/16  | 3.625   | 3/8       | 5.0               |
| 1 9/16                | SFC-25T  | 2-19T              | 32648                        | 133.4                | 111.1 | 35.3    | 11.1 | 39.7   | 50.8   | 68.3    | 19.1  | 11.1  | 92.075  |           | 2.27              |
| 1 5/8                 | SFC-26T  | 2-110T             | 7901                         | 6 1/8                | 5 1/8 | 1 27/64 | 7/16 | 1 9/16 | 2      | 2 13/16 | 3/4   | 7/16  | 4.250   | 7/16      | 6.3               |
|                       |          |                    | 35144                        | 155.6                | 130.2 | 36.1    | 11.1 | 39.7   | 50.8   | 71.4    | 19.1  | 11.1  | 107.950 |           | 2.86              |
| 1 11/16               | SFC-27T  | 2-111T             | 7901                         | 6 1/8                | 5 1/8 | 1 27/64 | 7/16 | 1 9/16 | 2      | 2 15/16 | 3/4   | 7/16  | 4.250   | 7/16      | 6.3               |
| 1 3/4                 | SFC-28T  | 2-112T             | 35144                        | 155.6                | 130.2 | 36.1    | 11.1 | 39.7   | 50.8   | 74.6    | 19.1  | 11.1  | 107.950 |           | 2.86              |
| 1 15/16               | SFC-31T  | 2-115T             | 7889                         | 6 1/8                | 5 1/8 | 1 25/64 | 7/16 | 1 5/8  | 2 3/32 | 3 3/8   | 3/4   | 15/32 | 4.250   | 7/16      | 7.1               |
| 2                     | SFC-32RT | 1-2T               | 35090                        | 155.6                | 130.2 | 35.3    | 11.1 | 41.3   | 53.2   | 85.7    | 19.1  | 11.9  | 107.950 |           | 3.22              |
|                       | SFC-32T  | 2-2T               | 9752                         | 6 3/8                | 5 3/8 | 1 19/32 | 7/16 | 1 5/8  | 2 1/4  | 3 1/2   | 7/8   | 5/8   | 4.500   | 7/16      | 8.1               |
|                       |          |                    | 43377                        | 161.9                | 136.5 | 40.5    | 11.1 | 41.3   | 57.2   | 88.9    | 22.2  | 15.9  | 114.300 |           | 3.67              |
| 2 1/8                 | SFC-34T  | 2-22T              | 9752                         | 6 3/8                | 5 3/8 | 1 19/32 | 7/16 | 1 5/8  | 2 1/4  | 3 5/8   | 7/8   | 5/8   | 4.500   | 7/16      | 8.1               |
| 2 3/16                | SFC-35T  | 2-23T              | 43377                        | 161.9                | 136.5 | 40.5    | 11.1 | 41.3   | 57.2   | 92.1    | 22.2  | 15.9  | 114.300 |           | 3.67              |
| 2 1/4                 | SFC-36T  | 2-24T              | 11789                        | 7 1/8                | 6     | 1 25/32 | 1/2  | 1 3/4  | 2 5/8  | 4 1/16  | 1     | 7/8   | 5.000   | 1/2       | 11.7              |
|                       |          |                    | 52437                        | 181.0                | 152.4 | 45.2    | 12.7 | 44.5   | 66.7   | 103.2   | 25.4  | 22.2  | 127.000 |           | 5.31              |
| 2 3/8                 | SFC-38T  | 2-26T              | 11789                        | 7 1/8                | 6     | 1 25/32 | 1/2  | 1 3/4  | 2 5/8  | 4 1/8   | 1     | 7/8   | 5.000   | 1/2       | 11.7              |
| 2 7/16                | SFC-39T  | 2-27T              | 52437                        | 181.0                | 152.4 | 45.2    | 12.7 | 44.5   | 66.7   | 104.8   | 25.4  | 22.2  | 127.000 |           | 5.31              |

## SFC-T Series Standard Piloted Flange Cartridge - SKWEZLOC Locking Collar - Metric -SKWEZ™

| BORE DIAMETER<br>mm | PART No.   | BEARING INSERT No. | BASIC DYNAMIC RATING<br>N/lb | DIMENSIONS mm / inch |       |         |      |        |        |         |        |       |         | BOLT SIZE | UNIT Wt.<br>kg/lb |
|---------------------|------------|--------------------|------------------------------|----------------------|-------|---------|------|--------|--------|---------|--------|-------|---------|-----------|-------------------|
|                     |            |                    |                              | A                    | BC    | D       | G    | H      | J      | L       | N      | O     | P       |           |                   |
| 30                  | SFC-206TMC | 5206TMC            | 19487                        | 111.1                | 92.1  | 29.8    | 9.5  | 34.9   | 41.3   | 55.6    | 15.9   | 6.4   | 76.200  | M10       | 1.45              |
|                     |            |                    | 4381                         | 4 3/8                | 3 5/8 | 1 11/64 | 3/8  | 1 3/8  | 1 5/8  | 2 3/16  | .63    | 1/4   | 3.000   |           | 3.2               |
| 35                  | SFC-207TMC | 5207TMC            | 25718                        | 127.0                | 104.8 | 32.5    | 9.5  | 34.9   | 44.5   | 65.1    | 17.5   | 9.5   | 85.725  | M12       | 1.91              |
|                     |            |                    | 5782                         | 5                    | 4 1/8 | 1 9/32  | 3/8  | 1 3/8  | 1 3/4  | 2 9/16  | 1 1/16 | 3/8   | 3.375   |           | 4.2               |
| 40                  | SFC-208TMC | 5208TMC            | 32648                        | 133.4                | 111.1 | 35.3    | 11.1 | 39.7   | 50.8   | 68.3    | 19.1   | 11.1  | 92.075  | M12       | 2.27              |
|                     |            |                    | 7340                         | 5 1/4                | 4 3/8 | 1 25/64 | 7/16 | 1 9/16 | 2      | 2 11/16 | 3/4    | 7/16  | 3.625   |           | 5                 |
| 45                  | SFC-209TMC | 5209TMC            | 35144                        | 155.6                | 130.2 | 36.1    | 11.1 | 39.7   | 50.8   | 74.6    | 19.1   | 11.1  | 107.950 | M14       | 2.86              |
|                     |            |                    | 7901                         | 6 1/8                | 5 1/8 | 1 27/64 | 7/16 | 1 9/16 | 2      | 2 15/16 | 3/4    | 7/16  | 4.250   |           | 6.3               |
| 50                  | SFC-210TMC | 5210TMC            | 35090                        | 155.6                | 130.2 | 35.3    | 11.1 | 41.3   | 53.2   | 85.7    | 19.1   | 11.9  | 107.950 | M14       | 3.22              |
|                     |            |                    | 7889                         | 6 1/8                | 5 1/8 | 1 25/64 | 7/16 | 1 5/8  | 2 3/32 | 3 3/8   | 3/4    | 15/32 | 4.250   |           | 7.1               |
| 55                  | SFC-211TMC | 5211TMC            | 43377                        | 161.9                | 136.5 | 40.5    | 11.1 | 41.3   | 57.2   | 92.1    | 22.2   | 15.9  | 114.300 | M14       | 3.67              |
|                     |            |                    | 9752                         | 6 3/8                | 5 3/8 | 1 19/32 | 7/16 | 1 5/8  | 2 1/4  | 3 5/8   | 7/8    | 5/8   | 4.500   |           | 8.1               |
| 60                  | SFC-212TMC | 5212TMC            | 52437                        | 181.0                | 152.4 | 45.2    | 12.7 | 44.5   | 66.7   | 104.8   | 25.4   | 22.2  | 127.000 | M16       | 5.31              |
|                     |            |                    | 11789                        | 7 1/8                | 6     | 1 25/32 | 1/2  | 1 3/4  | 2 5/8  | 4 1/8   | 1      | 7/8   | 5.000   |           | 11.7              |

For Medium Duty SKWEZLOC Locking Collar Bearing Inserts see page G-93. For Replacement Lock Collar see page G-98.  
 Sizes 2 11/16 and above come standard with Time Saving™ Axial Groove. See page G-22 for more information.