


TYPE A
without flange rings



TYPE B
2 flange rings
+ 2 snap rings



TYPE C
2 BRL snap rings



TYPE D
2 flange rings

DO NOT USE THESE DRAFT DRAWINGS TO ORDER BEARINGS.
ASK CPM TECHNICAL SERVICE FOR DETAILED DRAWINGS
AND FOR DIFFERENT DIMENSIONS OR TYPES.

d	Dr	B	J	X	R min.	r min.	BASIC DYNAMIC RADIAL LOAD RATING Cr kN	BASIC STATIC RADIAL LOAD RATING Cor kN	TYPE	P / N
90	176,210	80,0	122,00	55,0	2,0	2,0	638,0	785,0	A	2791
100	139,650	37,0	116,40	22,0	1,5	1,5	212,6	314,0	A	2653
130	207,120	64,0	162,30	44,0	3,0	3,0	620,0	875,0	A	2768
140	264,447	102,0	186,00	70,0	4,0	4,0	1190,0	1555,0	A	2680
325	383,420	43,0	351,50	30,0	3,5	2,1	585,0	1355,0	A	2787
375	444,820	48,0	406,50	36,0	3,5	2,1	805,0	1185,0	A	2788
430	506,726	55,0	466,00	40,0	4,5	2,1	985,0	2410,0	A	2786
485	575,130	66,0	527,50	48,0	5,5	3,0	1310,0	3270,0	A	2789