



SINGLE ROW

DO NOT USE THESE DRAFT DRAWINGS TO ORDER BEARINGS.
 ASK CPM TECHNICAL SERVICE FOR DETAILED DRAWINGS
 AND FOR DIFFERENT DIMENSIONS OR TYPES.

d	D	B	R	r	S	D 1	E	d 1	BASIC DYNAMIC LOAD RATING Cr kN	BASIC STATIC LOAD RATING Cor kN	TYPE	P / N
20	42	16,0	0,6	0,3	1,5	33,0	36,8	28,6	27,5	27,9	SL 183004	2511
22	47	12,5	0,6	0,6	1,2	37,5	41,5	32,5	24,2	24,4	-	2856
50	90	23,0	1,1	1,1	1,0	76,0	81,5	65,0	94,0	114,0	SL 182210	2560
65	90	15,8	1,0	1,0	1,0	81,0	85,3	75,5	60,0	86,0	SIMILAR TO SL 182913	4343
70	100	18,8	1,0	1,0	1,0	87,5	92,3	81,0	79,0	114,0	SIMILAR TO SL 182914	4344
85	120	21,7	1,1	1,1	1,0	105,0	109,6	96,0	104,0	159,0	SIMILAR TO SL 182917	4345
140	190	30,0	1,5	1,5	2,0	172,0	180,5	159,0	226,0	392,0	SL 182928	2659
160	220	36,0	2,0	2,0	2,5	199,0	208,5	181,0	310,5	538,7	SL 182932	2658
190	260	42,0	2,0	2,0	2,0	235,0	245,0	212,0	445,0	800,0	SL 182938	2631
220	270	24,0	1,5	1,5	2,0	250,9	260,0	238,7	188,0	377,0	SL 181844	2622
240	300	28,0	2,0	2,0	2,0	279,0	288,6	262,1	265,0	520,0	SL 181848-E	2621
320	383	38,0	2,0	2,0	4,0	359,0	368,0	347,0	343,0	879,0	-	2580
360	430	41,0	2,1	2,1	4,0	402,0	414,0	387,0	478,0	1242,0	-	2581
400	480	48,0	2,1	2,1	4,0	450,0	463,0	430,0	648,0	1658,0	-	2582

