



DO NOT USE THESE DRAFT DRAWINGS TO ORDER BEARINGS. ASK CPM TECHNICAL SERVICE FOR DETAILED DRAWINGS AND FOR DIFFERENT DIMENSIONS OR TYPES. S.D. : SEE DRAWING.

d	D	B	b	P	Dp.1	Dp.2	n° x d1	n° x d2	α	BASIC DYNAMIC LOAD RATING Cr/Ca kN	BASIC STATIC LOAD RATING Cor/Coa KN	P / N
82	260	23,50	18,00	23,50	240	S. D.	6xM10	S. D.	35°	50,7 / -	86,1 / -	2445 - 2536
82	260	23,50	21,70	25,00	240	S. D.	6xM10	S. D.	35°	14,9 / -	24,9 / -	2477
130	205	24,80	24,80	25,40	190	145	12x6,8	12x6,8	50°	- / 79	- / 335	2568
130	210	22,00	22,00	22,00	-	149	-	12xM8	45°	78,5 / -	102 / -	2557
140	240	22,00	22,00	22,00	220	151	6xM10 3xM8	9x6,6	25°	120 / -	156 / -	2595
140	300	30,00	30,00	36,00	270	170	12xM16	12x18	35°	106,9 / -	213,4 / -	2574
150	230	30,00	30,00	30,00	-	-	-	-	45°	132 / 153	217 / 542	2778
192	330	52,00	53,00	53,00	305	215	16xM12	17xM12 15x13	30°	270 / -	460 / -	2547
200	250	24,00	24,00	24,00	-	-	-	-	35°	78,9 / -	121,2 / -	2417
200	290	24,00	24,00	24,00	270	-	6xM12	-	35°	70 / -	113 / -	2426
200	280	30,00	30,00	30,00	-	-	-	-	45°	145 / 169	283 / 708	2779
220	310	24,00	24,00	24,00	285	-	6xM12	-	35°	111 / -	244 / -	2774
240	440	53,00	53,00	60,00	400	280	16xM12	16x13,5	50°	- / 350	- / 1681	2569
250	320	45,00	45,00	45,00	-	-	-	-	30°	143 / -	162 / -	2150
260	430	66,00	62,00	77,00	400	290	24x15	20x16	40°	382 / -	795 / -	2549