



DO NOT USE THESE DRAFT DRAWINGS TO ORDER BEARINGS. ASK CPM TECHNICAL SERVICE FOR DETAILED DRAWINGS AND FOR DIFFERENT DIMENSIONS OR TYPES. S.D. : SEE DRAWING.

d	De	Di	B	b	P	Dp.1	Dp.2	n° x d1	n° x d2	α	BASIC DYNAMIC LOAD RATING	BASIC STATIC LOAD RATING	P / N
											Cr/Ca kN	Cor/Coa KN	
95	189,056	160	19	15	19	150	110	6 x M5	6 x 6,5	30°	44,9 / -	80,1 / -	2589
110	232,5	169	23	23	25	195	130	6 x M8	8 x 8,5	35°	- / 48,1	- / 190,1	4590
124	270	186,5	22	22	24	220	147	8 x M10	8 x 8,5	35°	90,6 / -	165 / -	2773
196	248,5	240	26	23,0	26	231	204	8 x M6	12 x 6,4	30°	50,2 / -	126,8 / -	2490
245	358,306	295	49,5	41,5	26	324	232	10 x M10	20 x 9	50°	- / 136	- / 760	2886
246	358,306	295	35	29	35	324	262	10 x M10	10 x 11	50°	- / 136	- / 760	2611
386	598	475	75	60	83	525	419	24 x M12	24 x 14	50°	- / 474	- / 2825	2570
417	598	500	75	52	83	540	450	18 x M12	18 x 14	50°	- / 387	- / 1694	2555
417	598	500	50	42	58	540	450	18 x M12	18 x 14	50°	- / 266	- / 1874	2644