



Shaft Dia. (in.)	AMI Unit #	List Price	Dimensions (in.)										Basic Load Rating (lbf.)		Weight (lb.)
			D	U	C	R	N	M	T	W	K	Z (UNC)	Dynamic Cr	Static Cor	
			3/4	UE204-12MZ20	200.35	1.8504	1.299	0.669	0.059	0.500	0.720	0.177	1.724	0.374	
1	UE205-16MZ20	249.30	2.0472	1.394	0.669	0.059	0.563	0.780	0.177	1.929	0.374	8-32	3150	1780	0.56
1-3/16	UE206-19MZ20	281.05	2.4409	1.567	0.748	0.059	0.626	0.874	0.201	2.185	0.374	8-32	4410	2540	0.86
1-1/4	UE206-20MZ20														0.80
1-1/4	UE207-20MZ20	311.40	2.8346	1.728	0.787	0.079	0.689	1.000	0.228	2.421	0.433	10-24	5820	3460	1.38
1-7/16	UE207-23MZ20									2.520					1.22
1-1/2	UE208-24MZ20	365.90	3.1496	1.976	0.827	0.079	0.748	1.189	0.244	2.677	0.433	10-24	6590	4020	1.74
1-11/16	UE209-27MZ20	398.30	3.3465	1.976	0.866	0.079	0.748	1.189	0.256	2.913	0.433	10-24	7420	4610	1.90
1-15/16	UE210-31MZ20	429.65	3.5433	2.071	0.906	0.079	0.748	1.283	0.256	3.189	0.571	1/4-20	7980	5220	2.24
2	UE211-32MZ20	631.75	3.9370	2.228	0.945	0.098	0.874	1.315	0.287	3.189	0.571	1/4-20	9700	6610	2.95
2-7/16	UE212-39MZ20	730.65	4.3307	2.622	1.024	0.098	1.000	1.563	0.303	4.055	0.687	5/16-18	11800	8120	4.05

NOTE: If RF is required, add "RF" after the part number. For more information please see page 92 on RF Patent Seals.

INTERCHANGES: PN-16T / INS-DL-100-CR